DATA SHEET

VARNALUX

COB LED STRIP 8W/M


24V DC | IP20 | 5 M ROLL | 320 LEDS/M | CRI > 90



APPLICATION

- Residential lighting
- Decorative lighting
- Accent lighting
- Indirect lighting
- Cove and cabinet lighting
- Uniform dot-free line light

AVAILABLE MODELS	
Color Temp	REF No
2200K	200079
2700K	200080
3000K	200081
4000K	200082
6000K	200083



DATA SHEET

VARNALUX

COB LED STRIP 8W/M

24V DC | IP20 | 5 M ROLL | 320 LEDS/M | CRI > 90

ELECTRICAL DATA	
Power	8W/m
Voltage	24V DC
Lead wires	Double-ended 15 cm, red and black (20#)

PHOTOMETRICAL DATA	
Temperature (Kelvin)	2200K, 2700K, 3000K, 4000K or 6000K
Light color	Warm, neutral or cool white
Luminous flux	800 lm/m
Color Rendering Index (CRI)	> 90 Ra
Luminous efficiency	> 90 lm/W (warm white > 80 lm/W)
Beam angle	Up to 170°
LED quantity	320 LEDs/m (COB)

CAPABILITIES	
Cuttable	Minimum cutting length 50mm
Adhesive backing	High-adhesive double-sided
Max. running length	5 m (longer: connect in parallel)
Waterproofing (optional)	IP65 with silicone tube or heat-shrink tube


LIFESPAN & WARRANTY	
Lifespan	50.000 hrs
Warranty	2 years

DIMENSIONS & PACKAGING	
Strip dimensions	5000 x 8 x 2.3 mm
Roll length	5 m
Packing	Anti-static bag per 5 m roll
Outer carton	60 rolls

ADDITIONAL INFORMATION	
LED type	COB
PCB	Two-sided PCB, electrolytic copper
IP Rating	IP20
Working temp.	-20 °C to +40 °C
Storage temp.	-20 °C to +45 °C
Min. bending diameter	> 1 cm

AVAILABLE MODELS

Color Temp	REF No
2200K	200079
2700K	200080
3000K	200081
4000K	200082
6000K	200083



Schematic drawing, not to scale. Dimensions in mm.

DATA SHEET

VARNALUX

COB LED STRIP 8W/M

24V DC | IP20 | 5 M ROLL | 320 LEDS/M | CRI > 90

USER MANUAL | HOW TO USE

STEP 1 **Unpack and check**

Take the reel out of its anti-static bag and check it for damage. Do not install a damaged strip.

STEP 2 **Turn off the power**

Switch off the power supply before starting any work. Installation must be done by a qualified person.

STEP 3 **Plan the run**

The maximum running length is 5 m; for more than 5 m connect in parallel. The total power of the strips must be below 80% of the power supply's maximum output.

STEP 4 **Cut to length**

Cut only at the cutting marks: minimum cutting length 50mm.

STEP 5 **Stick the strip**

Peel off the high-adhesive double-sided backing and press the strip on a clean surface. Avoid sharp objects and heat. Bending diameter must be > 1 cm; do not bend at a short distance.

STEP 6 **Connect**

Connect the double-ended lead wires to a DC24V constant-voltage supply: red = +, black = -. Match the polarities marked on the PCB.

STEP 7 **Waterproofing (optional)**

For IP65 the strip can be injected with a silicone tube or covered with a heat-shrink tube. Guard against water and moisture.

STEP 8 **Turn on the power**

Switch on the power supply and check that all LEDs light up.

PACKING INFO


In the box	1 x COB LED strip, 5 m reel (anti-static bag)

DATA SHEET

COB LED STRIP 8W/M

24V DC | IP20 | 5 M ROLL | 320 LEDS/M | CRI > 90

CONNECTION DIAGRAM



Match the polarities ('+' / '-') marked on the PCB. Lead wires: red and black. Power supply is not part of the strip.

SAFETY NOTICE:

- Installation and electrical connection must be done by a qualified person. Switch off the power before installation.
- Use a stable DC24V constant-voltage power supply. The total power of the strips on one supply must stay below 80% of its rated output.
- Match the polarities according to the '+' and '-' marks on the PCB. The maximum running length per power feed is 5 m; for longer runs connect in parallel.
- Avoid sharp objects touching the strip surface and avoid contact of the light area with high-temperature objects.
- Do not bend the strip at a short distance (minimum bending diameter > 1 cm) and do not tie it tightly with metal wire.
- Guard against water and moisture: IP20 versions are for dry locations only.
- This product is not a toy. Install it out of the reach of children.