DATA SHEET

VARNALUX

LED RECESSED SPOTLIGHT 7W

NON-DIMMABLE | CUTOUT Ø90 MM | 600 lm | 60° | 2700-6000K



APPLICATION

- Restaurants and shops
- Museums and exhibition halls
- Conference rooms
- Warehouses
- Home lighting

AVAILABLE MODELS	
Color Temp	REF No
2700K	200194
4000K	200196
6000K	200198

Ø110mm | 7W | 600 lm | 3 YEARS | 2700-6000K | NON-DIM Dimming | 60° Beam angle | Ø90 Cutout (mm)



DATA SHEET

VARNALUX

LED RECESSED SPOTLIGHT 7W

NON-DIMMABLE | CUTOUT Ø90 MM | 600 lm | 60° | 2700-6000K

GENERAL	
Product size (diameter)	110mm
Dimensions	Ø110 x H60 mm
Cutout	90mm
Weight	0.35 kg

ELECTRICAL DATA	
Power (consumption)	7W
Input voltage	100-240V AC, 50/60Hz
Max. current	0.085A
Power factor	> 0.9
Driver	Varnalux driver (separate from the lamp body)
Dimming	Non-dimmable


PHOTOMETRICAL DATA	
Colour temperature (Kelvin)	2700K / 4000K / 6000K
Luminous flux	2700K: 525 lm, 4000K: 560 lm, 6000K: 600 lm
Colour rendering index (CRI)	> 80
LED brand	Sanan
Beam angle	60°
LED type	COB LED

LIFESPAN & WARRANTY	
Warranty	3 years

ADDITIONAL INFORMATION	
Housing	Aluminium-magnesium alloy + tempered glass

AVAILABLE MODELS

Color Temp	REF No
2700K	200194
4000K	200196
6000K	200198



Cutout Ø90 mm

Schematic drawing, not to scale. Dimensions in mm.

DATA SHEET

VARNALUX

LED RECESSED SPOTLIGHT 7W

NON-DIMMABLE | CUTOUT Ø90 MM | 600 lm | 60° | 2700-6000K

INSTALLATION

STEP 1 **Unpack and check**

Check the integrity of the product when unpacking. Installation must be done by a professional.

STEP 2 **Turn off the power**

Power must be cut off before installation. Make sure the switch is off before connecting to the power supply.

STEP 3 **Make a hole**

Make a hole of Ø90 mm in the ceiling (picture step 1).

STEP 4 **Connect the power wire**

Connect the power wire to the driver (picture step 2). The connection of the power supply must be sealed.

STEP 5 **Push the spring**

Push the spring(s) of the lamp body to the side (picture step 3).

STEP 6 **Insert the lamp**

Put the lamp into the hole (picture step 4) and release the springs.

STEP 7 **Dimming**

Non-dimmable version: do not use the lamp on a dimmer circuit.

STEP 8 **Switch on**

Switch on the power supply and check the light output.

PACKING INFO


In the box	1 x lamp body, 1 x driver (separate)

DATA SHEET

LED RECESSED SPOTLIGHT 7W

NON-DIMMABLE | CUTOUT Ø90 MM | 600 lm | 60° | 2700-6000K

CONNECTION DIAGRAM



Non-dimmable version: do not use on a dimmer circuit.

SAFETY NOTICE:

- Read the specification first and make sure the service environment matches the conditions in the specification before using.
- Confirm the applicable power supply before using.
- Make sure the switch is off before connecting to the power supply, to prevent electric shock.
- Operation against the rules may damage your property and even harm your personal safety.
- Preliminarily estimate the required quantity of lights and, from the power rating of a single light, the total power and the power supply plan.
- Dangerous high voltage: non-professionals are not allowed to maintain the product. A damaged exterior flexible cable or wire must be exchanged by the supplier, its agent or similarly qualified personnel.